
supervisorctl-serialrestart Documentation

Release 0.1.1

Sven Richter

Sep 27, 2017

Contents

1	Supervisor serialrestart	3
2	Installation	5
3	Usage	7
4	Contributing	9
4.1	Types of Contributions	9
4.2	Get Started!	10
4.3	Pull Request Guidelines	10
4.4	Tips	11
5	Credits	13
5.1	Development Lead	13
5.2	Contributors	13
6	History	15
6.1	0.1.1 (2013-10-29)	15
6.2	0.1.0 (2013-10-16)	15
7	Indices and tables	17

Contents:

CHAPTER 1

Supervisor serialrestart

Adds `serialrestart` command to [Supervisor](<http://supervisord.org/>). This command works similar to `restart` but if you have multiple services, it sometimes is preferable to restart them one after another to minimize downtime.

It even supports wildcards.

- Free software: BSD license
- Documentation: <http://supervisor-serialrestart.rtfld.org>.

CHAPTER 2

Installation

At the command line:

```
$ easy_install supervisor-serialrestart
```

Or:

```
$ pip install supervisor-serialrestart
```

And then add into your supervisor.conf:

```
[ctlplugin:serialrestart]
supervisor.ctl_factory = supervisorserialrestart.controllerplugin:make_serialrestart_
↪controllerplugin
```


CHAPTER 3

Usage

```
supervisor> status
baz:bar                RUNNING
baz:foo                RUNNING
one                    RUNNING
```

```
supervisor> serialrestart all
baz:bar: stopped
baz:bar: started
baz:foo: stopped
baz:foo: started
one: stopped
one: started
```

```
supervisor> serialrestart baz:*
baz:bar: stopped
baz:bar: started
baz:foo: stopped
baz:foo: started
```

```
$supervisor> serialrestart baz:b*
baz:bar: stopped
baz:bar: started
```


Contributions are welcome, and they are greatly appreciated! Every little bit helps, and credit will always be given. You can contribute in many ways:

Types of Contributions

Report Bugs

Report bugs at <https://github.com/native2k/supervisor-serialrestart/issues>.

If you are reporting a bug, please include:

- Your operating system name and version.
- Any details about your local setup that might be helpful in troubleshooting.
- Detailed steps to reproduce the bug.

Fix Bugs

Look through the GitHub issues for bugs. Anything tagged with “bug” is open to whoever wants to implement it.

Implement Features

Look through the GitHub issues for features. Anything tagged with “feature” is open to whoever wants to implement it.

Submit Feedback

The best way to send feedback is to file an issue at <https://github.com/native2k/supervisor-serialrestart/issues>.

If you are proposing a feature:

- Explain in detail how it would work.
- Keep the scope as narrow as possible, to make it easier to implement.
- Remember that this is a volunteer-driven project, and that contributions are welcome :)

Get Started!

Ready to contribute? Here's how to set up *supervisor-serialrestart* for local development.

1. Fork the *supervisor-serialrestart* repo on GitHub.
2. Clone your fork locally:

```
$ git clone git@github.com:your_name_here/supervisor-serialrestart.git
```

3. Install your local copy into a virtualenv. Assuming you have virtualenvwrapper installed, this is how you set up your fork for local development:

```
$ mkvirtualenv supervisor-serialrestart
$ cd supervisor-serialrestart/
$ python setup.py develop
```

4. Create a branch for local development:

```
$ git checkout -b name-of-your-bugfix-or-feature
```

Now you can make your changes locally.

5. When you're done making changes, check that your changes pass flake8 and the tests, including testing other Python versions with tox:

```
$ flake8 supervisorserialrestart tests
    $ python setup.py test
$ tox
```

To get flake8 and tox, just pip install them into your virtualenv.

6. Commit your changes and push your branch to GitHub:

```
$ git add .
$ git commit -m "Your detailed description of your changes."
$ git push origin name-of-your-bugfix-or-feature
```

7. Submit a pull request through the GitHub website.

Pull Request Guidelines

Before you submit a pull request, check that it meets these guidelines:

1. The pull request should include tests.

2. If the pull request adds functionality, the docs should be updated. Put your new functionality into a function with a docstring, and add the feature to the list in README.rst.
3. The pull request should work for Python 2.6, and 2.7 and for PyPy. Check https://travis-ci.org/native2k/supervisor-serialrestart/pull_requests and make sure that the tests pass for all supported Python versions.

Tips

To run a subset of tests:

```
$ python -m unittest tests.test_supervisor-serialrestart
```


CHAPTER 5

Credits

Development Lead

- Sven Richter <native2k@gmail.com>

Contributors

None yet. Why not be the first?

0.1.1 (2013-10-29)

- just fixed documentation/project structure

0.1.0 (2013-10-16)

- First release on PyPI.

CHAPTER 7

Indices and tables

- `genindex`
- `modindex`
- `search`